

SWF系列混流式 (斜流式) 风机

SWF系列混流式
(斜流式) 风机

安装使用说明书



SWF-I系列混流式(斜流式)风机性能参数表

型号	转速 (r/min)	序号	推荐工况 全压风量 (m³/h)	推荐工况 全压 (pa)	配用电机		A声级 dB(A)	重量 (kg)
					型号	功率 (kw)		
№2.5	2900	1	2664	358	Y801-2	0.75	≤72	42
		2	253	426				
		3	1935	482				
		4	1684	543				
		5	1532	635				
	1450	1	1362	96	Y7124	0.18	≤64	36
		2	1232	117				
		3	1020	126				
		4	850	147				
		5	743	166				
	960	1	902	54	Y6326	0.08	≤58	36
		2	746	66				
		3	675	78				
		4	563	83				
		5	492	98				
№3	2900	1	4652	512	Y90L-2	2.2	≤73	67
		2	4410	562				
		3	4018	691				
		4	3605	816				
		5	3212	883				
	1450	1	2312	121	Y7124	0.25	≤66	45
		2	2202	138				
		3	2009	184				
		4	1803	216				
		5	1606	236				
	960	1	1512	67	Y6326	0.12	≤60	40
		2	1436	93				
		3	1320	112				
		4	1164	127				
		5	1000	139				
№3.5	2900	1	5745	564	Y100L-2	3	≤75	85
		2	5317	623				
		3	4928	741				
		4	4542	876				
		5	4127	986				
	1450	1	3320	125	Y7124	0.25	≤68	48
		2	3082	141				
		3	2876	174				
		4	2447	216				
		5	2130	256				
	960	1	1938	79	Y7116	0.18	≤62	48
		2	1743	89				
		3	1592	103				
		4	1380	127				
		5	1234	146				

型号	转速 (r/min)	序号	推荐工况 全压风量 (m³/h)	推荐工况 全压 (pa)	配用电机		A声级 dB(A)	重量 (kg)
					型号	功率 (kw)		
№4	2900	1	7228	654	Y112M-2	4	≤72	100
		2	6801	715				
		3	6221	883				
		4	5688	1107				
		5	5242	1248				
	1450	1	4512	128	Y7124	0.37	≤64	52
		2	4302	143				
		3	3636	175				
		4	3053	212				
		5	2765	285				
	960	1	2642	86	Y7126	0.25	≤58	52
		2	2486	107				
		3	2237	129				
		4	1985	145				
		5	1743	156				
№4.5	2900	1	9169	672	Y132S-2	5.5	≤64	125
		2	8731	753				
		3	8159	928				
		4	7561	1187				
		5	7124	1298				
	1450	1	4728	182	Y802-4	0.55	≤80	70
		2	4552	207				
		3	4040	218				
		4	3392	265				
		5	3160	306				
	960	1	3592	88	Y7126	0.25	≤73	65
		2	3264	107				
		3	2892	132				
		4	2576	148				
		5	2240	162				
№5	2900	1	13110	801	Y132S-2	5.5	≤83	135
		2	12410	859				
		3	11865	1048				
		4	11342	1212				
		5	9876	1316				
	1450	1	8652	796	Y90S-4	1.1	≤77	80
		2	7433	220				
		3	6664	278				
		4	5252	326				
		5	4896	382				
	960	1	5624	96	Y8026	0.37	≤68	75
		2	4984	124				
		3	4322	136				
		4	3778	158				
		5	3215	182				

型号	转速 (r/min)	序号	推荐工况全压风量 (m³/h)	推荐工况全压 (pa)	配用电机		A声级 dB(A)	重量 (kg)
					型号	功率 (Kw)		
№5.5	2900	1	16820	825	Y132S-2	7.5	≤84	145
		2	15764	936				
		3	14562	1128				
		4	13450	1229				
		5	12264	1338				
	1450	1	9126	258	Y90L-4	1.5	≤78	100
		2	8445	296				
		3	7938	328				
		4	7431	354				
		5	6925	385				
	960	1	6532	119	Y8036	0.55	≤69	90
		2	5796	134				
		3	5257	148				
		4	4893	175				
		5	4265	206				
№6	2900	1	19230	836	Y132S-2	7.5	≤85	155
		2	18220	962				
		3	17824	1143				
		4	17210	1256				
		5	15210	1365				
	1450	1	11625	165	Y90L-4	1.5	≤79	110
		2	10000	200				
		3	8900	262				
		4	8121	325				
		5	7560	382				
	960	1	8025	128	Y90S-6	0.75	≤70	105
		2	7129	142				
		3	6283	176				
		4	5567	205				
		5	4986	236				
№6.5	1450	1	25124	524	Y132S-4	7.5	205	205
		2	23984	658				
		3	23044	832				
		4	21864	952				
		5	18671	1038				
	1450	1	15064	282	Y100L-4	2.2	145	145
		2	13660	315				
		3	12255	350				
		4	10840	382				
		5	9424	418				
	960	1	10544	155	Y90S-6	0.75	125	125
		2	9562	178				
		3	8578	198				
		4	7588	215				
		5	7540	238				

型号	转速 (r/min)	序号	推荐工况全压风量 (m³/h)	推荐工况全压 (pa)	配用电机		A声级 dB(A)	重量 (kg)
					型号	功率 (Kw)		
№7	1450	1	31380	608	Y116M-4	11	≤84	250
		2	29880	765				
		3	28805	968				
		4	27330	1107				
		5	24820	1248				
	1450	1	18800	329	Y100L-4	3	≤81	175
		2	17075	370				
		3	15319	404				
		4	13550	441				
		5	11780	470				
	960	1	13820	186	Y90L-6	1.1	≤74	150
		2	11952	202				
		3	10724	228				
		4	9485	257				
		5	8246	278				
№7.5	2900	1	30627	712	Y1601M-4	11	≤87	265
		2	29012	893				
		3	27232	1052				
		4	25518	1187				
		5	23422	1298				
	1450	1	22538	378	Y112M-4	4	≤82	195
		2	20490	420				
		3	18382	465				
		4	16260	504				
		5	14136	548				
	960	1	15776	208	Y100L-6	1.5	≤76	165
		2	14343	231				
		3	12867	256				
		4	11382	278				
		5	9895	298				
№8	1450	1	37350	801	Y160L-4	15	≤90	285
		2	35380	992				
		3	33210	1186				
		4	31120	1212				
		5	28564	1316				
	960	1	25467	196	Y132W-6	4	≤82	220
		2	22424	292				
		3	18636	382				
		4	17129	448				
		5	16269	516				
	720	1	19185	116	Y112W-8	1.5	≤75	195
		2	16818	175				
		3	13977	232				
		4	12846	272				
		5	11528	315				