

HKF后倾高效离心风机

HKF后倾高效
离心风机

安装使用说明书



HKF 4E-风机性能参数表

转速 r/min	流量 r/min	全压 (pa)	静压 (pa)	内效率 %	内功率 Kw	噪声 dB(A)	电动机	
							型号	功率
3000	8523	2613	2560	73	8.48	86.5	Y160M ₂ -2	15KW
	9945	2560	2489	75	9.43	87.5		
	11367	2471	2373	76	10.27	88.3		
	12789	2276	2151	77	10.50	88.6		
	14212	2154	2000	76	11.17	89.1		
	15634	1991	1804	74	11.69	89.3		
2750	17056	1796	1582	71	11.98	89.5	Y160M ₁ -2	11KW
	7813	2196	2151	73	6.53	84.6		
	9116	2151	2091	75	7.26	85.6		
	10420	2076	1994	76	7.91	86.4		
	11724	1912	1808	77	8.09	86.7		
	13027	1808	1681	76	8.61	87.2		
2400	14331	1673	1516	74	9.00	87.4	Y132S ₂ -2	5.5KW
	15635	1509	1330	71	9.23	87.7		
	6818	1673	1638	73	4.34	81.7		
	7956	1638	1593	75	4.83	82.7		
	9094	1582	1519	76	5.26	83.5		
	10232	1456	1377	77	5.38	83.8		
2200	11369	1377	1280	76	5.72	84.2	Y132S ₁ -2	5.5KW
	12507	1274	1155	74	7.98	84.5		
	13645	1146	1013	71	6.15	84.8		
	6250	1405	1377	73	3.34	79.8		
	7293	1377	1338	75	3.72	80.8		
	8336	1329	1276	76	4.05	81.6		
1950	9379	1224	1157	77	4.14	81.8	Y112M-2	4KW
	10422	1157	1076	76	4.61	82.3		
	11465	1071	970	74	4.61	82.6		
	12508	966	851	71	4.73	82.8		
	5540	1104	1082	73	2.33	77.2		
	6464	1082	1052	75	2.59	78.2		
1750	7389	1044	1003	76	2.82	78.9	Y100L ₂ -4	3KW
	8313	961	909	77	2.88	79.2		
	9238	909	845	76	3.07	80.0		
	10162	841	762	74	3.21	79.9		
	11086	759	669	71	3.29	80.0		
	4972	889	871	73	1.68	74.8		
1600	5801	871	847	75	1.87	75.8	Y110L ₁ -4	2.2KW
	6631	841	808	76	2.04	76.8		
	7461	774	732	77	2.08	76.9		
	8290	732	681	76	2.22	77.4		
	9120	678	614	74	2.32	77.8		
	9949	611	538	71	2.38	72.9		
1350	4545	743	728	73	1.29	72.9	Y90L-4	1.5KW
	5304	728	708	75	1.43	73.9		
	6063	703	675	76	1.56	74.7		
	6821	647	612	77	1.59	74.9		
	7580	612	569	76	1.70	75.4		
	8338	566	513	74	1.77	75.7		
1350	9097	511	450	71	1.82	76.0	Y90L-4	1.5KW
	3835	529	518	73	0.77	69.2		
	4475	518	504	75	0.86	70.2		
	5115	500	481	76	0.94	71.0		
	5755	461	436	77	0.96	71.3		
	6395	436	405	76	1.02	71.7		
1350	7035	403	365	74	1.07	72.0	Y90L-4	1.5KW
	7675	364	320	71	1.09	72.2		

HKF 4.5E-风机性能参数用表

转速 r/min	流量 r/min	全压 (pa)	静压 (pa)	内效率 %	内功率 Kw	噪声 dB(A)	电动机	
							型号	功率
2700	10922	2679	2624	73	11.13	87.8	Y160L-2	18.5KW
	12744	2624	2552	75	12.39	88.8		
	14566	2533	2433	76	13.49	89.6		
	16389	2333	2205	77	13.79	89.6		
	18212	2202	2050	76	14.68	90.4		
	20031	2041	1850	74	15.35	90.6		
	21856	1841	1622	71	15.74	90.8		
2500	10112	2297	2250	73	8.84	86.2	Y160M ₂ -2	15KW
	11800	2250	2188	75	9.83	87.2		
	13487	2172	2086	76	10.71	87.9		
	15175	2000	1891	77	10.95	88.2		
	16863	1891	1758	76	11.65	88.7		
	18550	1750	1586	74	12.19	88.9		
	20237	1578	1391	71	12.50	89.0		
2250	9101	1860	1822	73	6.44	83.9	Y160M ₁ -2	11KW
	10620	1822	1772	75	7.17	84.9		
	12139	1759	1690	76	7.81	85.6		
	13658	1620	1531	77	7.98	85.9		
	15176	1531	1424	76	8.50	86.4		
	16695	1417	1285	74	8.88	86.6		
	18214	1278	1126	71	9.11	86.8		
2000	8090	1470	1440	73	4.53	81.3	Y132S ₂ -2	7.5KW
	9440	1440	1400	75	5.04	82.3		
	10790	1390	1335	76	5.48	83.1		
	12140	1280	1210	77	5.61	83.4		
	13490	1210	1125	76	5.97	83.6		
	14840	1120	1015	74	6.24	84.1		
	16190	1010	890	71	6.40	84.3		
1800	7281	1191	1166	73	3.30	79.0	Y132S ₁ -2	5.5KW
	8496	1166	1134	75	3.67	80.0		
	9711	1126	1081	76	4.00	80.8		
	10926	1037	980	77	4.09	81.1		
	12141	980	911	76	4.35	81.6		
	13356	907	822	74	4.55	81.7		
	14571	818	721	71	4.66	82.0		
1750	6472	941	922	73	2.32	76.5	Y112M-4	4KW
	7552	922	896	75	2.58	77.5		
	8632	890	854	76	2.81	78.2		
	9712	819	774	77	2.87	78.5		
	10792	774	720	76	3.06	79.0		
	11872	717	650	74	3.19	79.2		
	12952	646	570	71	3.28	79.5		
1450	5865	773	757	73	1.72	74.3	Y110L ₂ -4	3KW
	6844	757	736	75	1.92	75.3		
	7823	731	702	76	2.09	76.1		
	8802	673	636	77	2.14	76.4		
	9780	636	591	76	2.27	76.9		
	10759	589	534	74	2.38	77.1		
	11738	531	468	71	2.44	77.3		
1300	5258	621	608	73	1.24	72.0	Y110L ₁ -4	2.2KW
	6136	608	592	75	1.38	73.0		
	7013	587	564	76	1.51	73.7		
	7891	541	511	77	1.54	74.0		
	8769	511	475	76	1.64	74.5		
	9646	473	429	74	1.71	74.7		
	10523	427	376	71	1.76	74.9		

HKF 5E-风机性能参数表

转速 r/min	流量 r/min	全压 (pa)	静压 (pa)	内效率 %	内功率 Kw	噪声 dB(A)	电动机	
							型号	功率
2200	12217	2194	2147	73	10.20	86.3	Y160L-2	18.5KW
	14250	2151	2087	75	11.21	86.8		
	16280	2065	1981	76	12.13	87.3		
	18319	1914	1807	77	12.33	87.8		
	20357	1807	1676	76	13.27	88.3		
	22396	1678	1521	74	13.92	88.8		
	24435	1506	1319	71	14.19	89.3		
2100	11662	1999	1956	73	8.87	85.3	Y160M-2	15KW
	13608	1960	1901	75	9.75	85.8		
	15540	1882	1805	76	10.55	86.3		
	17486	1744	1646	77	10.73	86.8		
	19432	1646	1527	76	11.54	87.3		
	21378	1529	1386	74	12.10	87.8		
	23324	1372	1201	71	12.35	88.3		
1900	10554	1637	1601	73	6.57	83.1	Y160M-2	11KW
	12312	1604	1556	75	7.22	83.6		
	14060	1540	1478	76	7.81	84.1		
	15821	1428	1348	77	7.94	84.6		
	17581	1348	1250	76	8.55	85.1		
	19342	1251	1134	74	8.97	85.6		
	21103	1123	983.5	71	9.14	86.1		
1700	9441	1310	1282	73	4.71	80.7	Y132M-4	7.5KW
	11016	1284	1246	75	5.17	81.2		
	12580	1233	1183	76	5.60	81.7		
	14155	1143	1079	77	5.69	82.2		
	15731	1079	1001	76	6.12	82.7		
	17306	1002	908	74	6.42	83.2		
	18881	899	787	71	6.55	83.7		
1500	8330	1020	998	73	3.23	78.0	Y132S-4	5.5KW
	9720	1000	970	75	3.55	78.5		
	11100	960	921	76	3.84	79.0		
	12490	890	840	77	3.91	79.5		
	13880	840	779	76	4.21	80.0		
	15270	780	707	74	4.41	80.5		
	16660	700	613	71	4.50	81.0		
1350	7497	826	808	73	2.36	75.7	Y112M-4	4KW
	8748	810	786	75	2.59	76.2		
	9990	778	746	76	2.80	76.7		
	11241	721	680	77	2.85	77.2		
	12492	680	631	76	3.07	77.7		
	13743	632	573	74	3.22	78.2		
	14994	567	497	71	3.28	78.7		
1200	6664	653	639	73	1.66	13.2	Y110L-4	3KW
	7776	640	621	75	1.82	73.7		
	8880	614	589	76	1.97	74.2		
	9992	570	538	77	2.00	74.7		
	11104	538	499	76	2.15	75.2		
	12216	499	453	74	2.26	75.7		
	13328	448	392	71	2.30	76.2		
1100	6109	549	537	73	1.28	71.3	Y110L-4	2.2KW
	7128	538	522	75	1.40	71.8		
	8140	516	495	76	1.52	72.3		
	9159	479	452	77	1.54	72.8		
	10179	452	419	76	1.66	73.3		
	11198	420	380	74	1.74	73.8		
	12217	376	330	71	1.77	74.3		