

SDKW-外转子 系列新风机

SDKW-外转子
系列新风机

安装使用说明书



SDKW-外转子新风机性能参数表

型号	推荐 工况	流量 (m3/h)	压力 (Pa)	噪声 dB(A)	电压 (V)	频率 (Hz)	功率 (Kw)	电流 (A)	极数 (P)	电容 (uF)	重量 (Kg)
SDKW-2.0AM2	1	1200	310	63	380	50	0.32	0.9	4		11
	2	1350	301	63							
	3	1590	296	62							
	4	1780	185	62							
	5	2000	280	61							
SDKW-2.0AM4-C	1	1200	315	63	220	50	0.25	1.8	4	6	11
	2	1380	307	63							
	3	1560	298	63							
	4	1710	189	62							
	5	1850	285	62							
SDKW-2.15AM3	1	1900	355	65	380	50	0.45	1.42	4		19
	2	2160	351	65							
	3	2380	348	64							
	4	2490	343	64							
	5	2650	340	64							
SDKW-2.15AM3-C	1	1900	355	65	220	50	0.45	1.42	4		19
	2	2160	351	65							
	3	2380	348	64							
	4	2490	343	64							
	5	2650	340	64							
SDKW-2.5AL1	1	2500	420	66	380	50	0.55	1.68	4		21
	2	2600	400	66							
	3	2800	380	65							
	4	3000	370	65							
	5	3300	360	64							
SDKW-2.5AL2	1	2500	510	67	380	50	0.75	2.3	4		22
	2	2650	480	67							
	3	2800	470	67							
	4	3000	460	66							
	5	3600	450	66							
SDKW-2.5AL2-C	1	2500	510	67	220	50	0.75	2.3	4		22
	2	2650	480	67							
	3	2800	470	67							
	4	3000	460	66							
	5	3600	450	66							
SDKW-2.5ASG2	1	4000	500	70	380	50	1.1	2.91	4		24
	2	4250	482	70							
	3	4560	476	69							
	4	4780	460	69							
	5	4900	450	69							
SDKW-2.8AL2	1	4000	530	71	380	50	1.5	3.5	4		29
	2	4620	510	71							
	3	5150	491	70							
	4	5600	477	70							
	5	6000	465	70							
SDKW-3.35AL1	1	6000	730	75	380	50	2.2	4.7	4		60
	2	6410	710	75							
	3	6670	690	75							
	4	6890	670	75							
	5	7200	680	75							

SDKW-外转子新风机性能参数表

型号	推荐 工况	流量(m3/h)	压力(Pa)	噪声 dB(A)	电压 (V)	频率 (Hz)	功率 (Kw)	电流 (A)	极数 (P)	电容 (uF)	重量 (Kg)
SDKW-3.35AL4	1	5000	440	70	380	50	1.5	3.5	4		60
	2	5300	430	70							
	3	5650	420	70							
	4	5900	410	70							
	5	6500	400	70							
SDKW-3.35AS3	1	6000	930	76	380	50	3	6.6	4		55
	2	6400	912	76							
	3	6800	880	76							
	4	7150	865	76							
	5	7500	850	76							
SDKW-3.55AL3	1	8000	950	78	380	50	4	8.2	4		75
	2	8900	940	78							
	3	10500	930	78							
	4	10750	920	78							
	5	11000	910	78							
SDKW-3.55AL5	1	6000	560	71	380	50	2.2	5.1	6		68
	2	6400	550	71							
	3	6850	540	71							
	4	7300	530	71							
	5	7500	520	71							
SDKW-4.0AL2	1	8000	600	75	380	50	3	6.5	6		82
	2	8900	550	75							
	3	10500	580	75							
	4	10750	595	75							
	5	11000	530	75							
SDKW-4.5AL2	1	11000	600	77	380	50	5.5	12.5	6		135
	2	11950	559	77							
	3	13450	568	77							
	4	15660	594	77							
	5	16000	550	77							
SDKW-4.5AL4	1	15000	700	79	380	50	7.5	15	6		175
	2	16000	685	79							
	3	17840	679	79							
	4	19567	660	79							
	5	22000	650	79							
SDKW-5.0AL2	1	16000	830	80	380	50	9	19	6		186
	2	17450	825	80							
	3	19560	814	80							
	4	22140	805	80							
	5	23000	800	80							